



ALAT UJI

Products, Solution, Services



PT TAHARICA

Jl. Radin Inten II No. 62 Duren Sawit - Jakarta 13440



0816 1740 8925 | 0816 1740 8927



muchlis@taharica.com



021 8690 6777



0857 1145 8285



www.taharica.com | www.alatuji.com

TESTING INSTRUMENT

Vibration Tester

TIME 7240



IDR.56.328.146
Negotiable

Specifications:

Sensitivity acceleration	Acceleraion	Velocity	Displacement
1.0 ~ 9.9	1-2,000	1-2,000	10-20,000
10 ~ 99	0.1-200	0.1-200	1-2,000
Acceleration : 5Hz ~ 10000Hz			
Frequency range	Velocity : 5Hz ~ 1000Hz		
	Displacement : 5Hz ~ 500Hz		
Rotation speed	300 ~ 6000RPM		
Operating Temperature	Li Battery(Continuous for 8hours)		
Humidity	≤ 80%RH		
Dimensions(mm)	223 x 122 x 38		
Weight(g)	606		

Features:

- Three channels(CH1, CH2 and REV) are available, the vibration of any two of the three directions including X axis, Y axis and Z axis can be tested.
- Five measuring modes: three parameters measuring (AVD mode), dynamic time domain waveform(TIME mode), dynamic spectrum measurement(FFT mode), data sampling (Sample mode), rotation speed measurement(REV mode).
- The peak value of acceleration, velocity and peak to peak value of displacement are measured.
- Preset the filter's cut-off frequency of pass band, frequency step is 100Hz.
- Dynamic display the waveform in real time.
- Dynamic display the vibration frequency.
- Continuous data sampling for 20 seconds
- With powerful data management:50 points stored

More information: Please send to sales@alatuji.com