

Multifunctional Moisture Meter MC-7825P/7825S/7825PS



Description

Ideal to use in solid floors, wood, wood products such as wood fiber materials, wooden articles, Chinese traditional medicine, tobacco, cotton paper, furniture, trailer, camper, boat, sensitive wood articles with smooth wood surfaces, suitable on rough wood surfaces like measurements of firewood, fireplace wood, firing wood, building timber, lumber, planks, boards, asbestos, asphalt, Bakelite, brick, cardboard and paper, charcoal, chipboard, concrete, felt, fiberboard, foam, glass (including quartz and organic glass), granite, leather, lime, marble, peat, plaster, rubber, sand, stone, wood and many more.

Feature

- * Equipped with 2 different testing methods, scanner and probes (SEARCH & PIN STEEL PROBES) to measure both wood and concrete dampness level
- * For use in a wide variety of situations and capable to tests a massive range of different materials
- * With Color coded LED lights, helps the user to map the extent of problems and monitor the changes in its condition precisely and reliably
- * DATA HOLD function to freeze the current value at the display
- * Provides alarm values that can be set by the user
- * With sleek design that fits snugly in the hand, so it can be used effortlessly for long periods
- * With easy to use hand held digital LCD display monitor with very bright for visual clarity and gives exact reading with no guessing errors
- * Can be switches off automatically after five minutes or switch off manually
- * Reliable and accurate testing results are guaranteed
- * Approved by strict quality and safety standards
- * Made from quality materials to ensure its DURABILITY for LONG and TROUBLE-FREE life
- * Measurement codes: 10 codes in pin mode and 20 codes in search mode
- * Search mode reads up to a depth of 50mm
- * 2 Pin Steel Probe Measurement: 1.5cm (0.5")



Spesification

Specifications	Model		MC-7825	
Model with suffix		Р	S	PS
Sensing type		Pin	Search	Pin&search
		type	type	type
Wood over 150 species		V		
Building moisture		0-50% (concrete)		
Measuring range	Moisture	0-80%		
Resolution		0.1		
Display		4 digits, 10mm LCD screen 3 Color Code LED light Indicator: GREEN light- represents safe & air-dry state YELLOW light - represents borderline state RED light - represents damp state		
Accuracy	Moisture	±0.5%n		
Power supply		4x1.5V AAA (UM-4) battery(not included)		
Battery indicator		Low battery indicator		
	Interface			no
Dimension(mm)		165x62x26		
Weight(Not including battery)		119g	114g	175g

Office: Jl. Radin Inten II No. 62 Duren Sawit, Jakarta 13440 - Indonesia Workshop: Jl. Pahlawan Revolusi No. 22B, Jakarta 13430 - Indonesia Phone: 021-8690 6777 (Hunting)

Mobile: +62 816 1740 8925 Fax: 021-8690 6771